



Q Series - Q.bloxx D104 Digital Input Module

Gantner
instruments



Most important features:

- **16 digital inputs**
state, single or bit set, host controlled
- **Configurable threshold**
TTL or high level (EN61131-2, Type1)
- **Short reaction time**
10 µs per input
- **RS485 fieldbus-interface**
up to 48 Mbps: LocalBus
up to 115.2 kbps: Modbus-RTU, ASCII
- **Connectable to any Test Controller**
e.g. Q.station, Q.gate or Q.pac
- **Galvanic isolation**
of I/O-signals (2 groups x 8 inputs), to power supply and to interface
Isolation voltage 500 VDC
- **Electromagnetic Compatibility**
according EN 61000-4 and EN 55011
- **Power supply 10...30 VDC**
- **DIN rail mounting (EN 60715)**

The Q-series has been designed for demanding measurements found in today's most industrial measuring and testing environments. The range of applications starts from single stand-alone solutions up to networked multi-channel applications in the field of component testing, engine testing, process performance testing and structural monitoring.

The range and flexibility of the modules allows an optimized solution for each single task: Dynamic signal acquisition up to 100 kHz, inputs and outputs for all types of signals, galvanic isolation of inputs and outputs, multi-channel solutions, high density packaging and intelligent signal conditioning.

Data exchange between Test Controller and automation level is communicated via Ethernet TCP/IP or fieldbus systems like EtherCAT or Profibus-DP and additional Ethernet-based industrial standards



Specifications

Digital Inputs	
Number	16
Input voltage	max. 30 VDC
Input current	max. 2 mA
Threshold (programmable)	TTL or
Signal voltage „0“	-3... 5 VDC (EN61131-2, Type1)
Signal voltage „1“	11... 30 VDC (EN61131-2, Type1)
Isolation Voltage	500 VDC, terminal 1/terminal 2 and against power supply and interface ¹
Function	
State	
Reaction time	10 µs
16-fold Bit-Set	specification such as simple state-input, but the binary coded information of 16 inputs can be transmitted as a single variable.
Power Supply	
Power supply	10 up to 30 VDC, overvoltage and overload protection
Power consumption	approx. 2 W
Influence of the voltage	<0.001 %/V
Environmental	
Operating temperature	-20°C up to +60°C
Storage temperature	-40°C up to +85°C
Relative humidity	5 % up to 95 % at 50°C, non condensing
Communication Interface	
Standard	RS-485, 2-wire
Data format	8e1
Protocols	Local-Bus: 115200 bps up to 48 Mbps
	Modbus-RTU, ASCII: 19200 bps up to 115200 bps
Connectable devices	max. 32
Mechanical	
Case	Aluminum and ABS
Dimensions (W x H x D)	27 x 120 x 105 mm
Weight	approx. 200 g
Mounting	DIN EN-rail

¹Noise pulses up to 1000 VDC, permanent up to 250 VDC

Valid from March 2012. Specification subject to change without notice