



Power:

Battery powered (150 hours runtime)

Wireless charging QI

Information given:

-Wind speed

Range: 1-25m/s (2.24-56 mph)

Accuracy: 0.3 m/s at 10 m/s (0.67 mph at 22.37 mph)

Threshold: 1 m/s (2.24 mph)

-Wind direction

Range: 0 - 359°

Accuracy: ±1°

Measurement:

-Sample rate

1 Hz

-Output units

m/s, km/h, knots, mph

Data Output:

-Bluetooth

Version 5.1

Range Up to 30 meters or 98 feet (free space)

Easy mount:

Tripod mount - Female thread



Sensors:

Ultrasonic transducers (4x)

Dimensions

Diameter: 43 mm (1.69 in.)

Height: 47 mm (1.85 in.)

Weight: 78 grams (2.75 oz.)

Environmental:

IP Code

IPX8 Protection Grade

Temperature range

-15/60° C if no frost

Humidity

0/100% HR

APP Compatibility:

Marine

GARMIN

Calypso Instruments Sailing

Anemotracker Weather4D

Sentinel Marine Solutions

iRegatta

eStela

Sail Racer

EDO sailing instruments

SailGrib

qtVlm Navigation and Routing

Tactiqs

Meteo

Weather File

Ballistics

Strelok Pro

Display Compatibility



Distributed by:

Emissions Measurement ♦ Drug + Alcohol ♦ Environmental Monitoring ♦ Post Harvest Technology

PACIFIC DATA SYSTEMS AUSTRALIA

27 High Tech Court, Eight Mile Plains, QLD, 4113

+617 3361 2000

sales@pacdatasys.com.au

www.pacdatasys.com.au